



Beautiful decor of a dream home

SKIMCOAT



PRODUCT DESCRIPTION

SkimCoat is a single component polymer modified Cement Based Joint Compound applicable to cover the common faults of Fair Faced Concretes. This product can be troweled or applied on a variety of vertical surfaces to create a seamless industrial concrete look with highly glossy and designed finish.



ANTI-ALGAL WITH DUST REPELLENCY



SMOOTH FINISH AND TEXTURE DESIGN



SELF-CURING & FAST DRYING



SUPERIOR ADHESION ON A VARIETY OF SURFACES



CRACK RESISTANT

PRODUCT INFORMATION

PACK SIZES



5 Kg

20 Kg

COVERAGE

WALL

3 COATS

20-22 SFT/kg



*Coverage mentioned is based on lab tests conducted under controlled environment

**Actual coverage is dependent on factors such as surface condition, application method, and application condition

UNIQUE FEATURE



SINGLE COMPONENT JUST MIX WITH WATER



APPLICABLE FOR BOTH INTERIOR AND EXTERIOR

SURFACE PREPARATION



Recommended Surfaces



Levelling



Feathering cementitious joints



Repairing



Screw-holes



Minor surface defects



Surface Preparation Method

Surface preparation:

All bases must be cured, sufficiently rigid, and clean of any surface contamination such as oil, dirt, grease, coatings, curing compounds, and laitance that may prevent proper adhesion. If necessary, clean the surface by shot blasting, scarifying, or light grinding. Any painted or coated surfaces should be sandblasted or grinded to remove existing coatings. If the concrete substrate is highly porous or absorptive or to increase the bonding between the substrate and the patching material, prime the surface of the concrete with Nitobond SBR Latex. All cracks larger than hairline shall be filled with Crack Fill Paste.

Remove all unsound concrete. For old concrete surfaces, it is recommended to water the surface of the concrete at least one day before application of the Skim Coat. Surface should be thoroughly cleaned from any resulting debris or dust by washing with clean water.

Berger offers a complete range of surface treatment solutions, please call 08000-123456 or visit your nearest Berger Experience Zone for more information.



METHOD OF APPLICATION



Surface should be pre-wetted before each coat



Apply 2 coats Self Curing Skim Coat with 4-6 hours interval



Apply 3rd coat as finish coat using steel trowel



Finish might be glossy or matt based on the application technique



MIXING RATIOS



Paint : Water = 2 : 1
(By volume)



ADDITIONAL INFORMATION

- ◆ Use at temperatures not below 5°C and not more than 35°C.
- ◆ Use for both internal and external purposes.
- ◆ Don't add any other products to the mix during or after mixing.
- ◆ Do not apply on direct sunlight.



ACCOMPANYING PRODUCT

N/A


















SHEEN SCALE

Based on application style sheen level can be both **MATT** or **GLOSSY**



PRODUCT SPECIFICATION

 SHADE/COLOR	03 no's	 % TOTAL SOLIDS (WEIGHT)	100	 METHOD OF APPLICATION	 STEEL TROWEL
 GLOSS / SHEEN LEVEL	Based on application style sheen level can be both matt or glossy	 PIGMENTATION	TITANIUM DIOXIDE IRON OXIDE YELLOW IRON OXIDE BACK	 VOC	Not Applicable as this is a solid paint
 TOUCH DRY		 CLEAN UP SOLVENT	 WATER	 VEHICLE	Cement and special type of polymer
 HARD DRY	 (Recoat)	 TYPE OF CURE	Self Curing		

Ingredients: Special cement, inorganic filler, acrylic binder and humectant etc.

*Please refer to MSDS for safety information

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be applied, we can only guarantee the quality of the product itself. We reserve the right to alter the given data without prior notice. Covering capacity is indicated based on results obtained on a prepared smooth surface.